

Vehicle Weighing Solutions

That Help Drive Your Business



Performance and Automation

for Reliable Data Integration

- Complete vehicle weighing solutions
- Flexible connectivity options
- Networked integration for ease of data access and analysis

Maximizing your operational performance requires a weighing system that provides you with accurate, reliable, and easy to understand information from your vehicle scale. While the vehicle scale itself is the foundation of your weighing system, without a high performance weighing terminal you will not maximize efficiency in your operations that depend on vehicle weight data.

Use of automation technology and data integration in vehicle weighing continues to expand into many applications and industries that previously used a "standalone" weighing terminal.









Data Integration

- PLC interface via EtherNet/IP, DeviceNetTM, Profibus[®], ControlNetTM or Modbus TCP
- Ethernet TCP/IP, serial, 4-20 mA analog output
- Optional Wi-Fi connectivity
- OPC for exchange of data between multi-vendor devices and control applications

Facility inbound/outbound vehicle weighing using a single truck scale





Networking multiple truck scales into a single database



Integration of truck scale operations with filling or load-out systems







Scale House

Back Office

Vehicle Software Solutions

Depending on the requirements of the application, one of a number of scale terminals with dedicated vehicle weighing software can be used.

For advanced weighing applications, METTLER TOLEDO OverDrive® PC-based software works together with a weighing terminal to provide capabilities such as an integrated MS SQL server database, multi-scale operation, contract pricing, credit card processing, video image integration, unattended weighing, and multi-lingual operation.



Interface with PowerCell® PDX® vehicle weighing technology

The power and flexibility of METTLER TOLEDO scale terminals enable you to apply them in the most demanding vehicle weighing applications. The latest generation of PowerCell®, the PowerCell® PDX® load cell, provides protection beyond traditional analog load cells, securing both the integrity of your process and your profits. Accurate vehicle scale weights are assured, day in and day out under the most severe of operating conditions, with predictive diagnostics constantly monitoring your scale and minimizing downtime costs.

PowerCell® PDX® networks guard against failure by providing monitoring and logging of a variety of factors that can affect system integrity:

- Weighing errors
- Overloads
- Network health
- Load cell enclosure integrity



Damage

Vehicle Weighing Scale Terminals





Included with Drive-780 software

EtherNet/IP, Profibus®, DeviceNet™, ControlNet™,

Modbus TCP, A-B RIO

	IND560	IND560 PDX	IND780
External QWERTY keyboard	Via optional USB interface		Via standard USB interface
Display	Graphic vacuum fluorescent, multi-line with prompting		1/4 VGA graphic color or monochorome
Serial ports, standard	1: RS232/422/485	2: RS232 and RS232/485	2: RS232 and RS232/485
Serial ports, optional	2 additional		2 additional
Ethernet TCP/IP	Optional		Standard
Load cell interface	Analog	PowerCell® PDX®	PowerCell® PDX® and MTX®, Analog
Max. number of load cells	8	14	24 PowerCell® PDX®
Max. number of scale channels	1		used with multi-platform scales for axle and total weights, plus metrologically approved sum scale
Optional software	Drive-560 Vehicle Software, TaskExpert™		Drive-780 Vehicle software, Axle-780 software, TaskExpert™
Languages supported	English, Spanish, French, German, Italian		English, Spanish, French, German, Swedish, Italian Chinese

Via custom TaskExpert™ program

EtherNet/IP, Profibus®, DeviceNet™,

Modbus TCP, A-B RIO

Unattended weighing

Traffic control using lights or gates

PLC Interface

Complete transactions quickly using the IND9U unattended scale controllers, which enable drivers to process their own vehicle weighing transactions in seconds. There is no need for a scale house with an operator on duty. An unattended system is ideal for remote locations, scales that operate around the clock, and facilities with multiple scales.

Wireless options simplify installation and operations in your facility by using wireless Ethernet to connect scale controllers to your communications infrastructure. Even intercom voice data can be sent wirelessly, using available Voice-Over-IP (VOIP) technology.





Dynamic Weighing Solutions

Increase Throughput and Productivity

METTLER TOLEDO provides weighing solutions for both rail and vehicle dynamic weighing that allow for enhanced operational productivity, particularly in high volume weighing applications.





Railcar Dynamic Weighing

The IND9R86 dynamic weighing controller, integrated with a METTLER TOLEDO dynamic rail scale, allows for automated weighing of entire trains as they cross the scale at speeds up to 6 mph. Individual rail car weights are obtained without uncoupling cars, and train total weights are automatically calculated. Rail car identification information from an RFID tag is integrated into the

weighing record. The controller stores and prints weight information for any length train, even those comprising several hundred cars, and provides data storage for hundreds of trains. IND9R86 is designed for both attended and fully unattended, remote applications. Legal for trade approvals are available for both NTEP and OIML requirements.


Vehicle Dynamic Weighing

METTLER TOLEDO vehicle Weigh in Motion (WIM) systems have

been in use for over 25 years in high volume highway weigh station applications. WIM systems allow trucks to be weighed at speeds up to 100 km/hr (65 mph), automatically making vehicle weight information available to higher level software applications for overweight vehicle enforcement operations.

WIM systems are also used at seaports where throughput of high volumes of trucks is critical, and truck weight information is automatically integrated into seaport container ship management software applications. As with truck weight enforcement systems, the WIM system can

include overview image and license plate reader data as part of the weighing record.



Hazardous Area Solutions

Compliance with Global Standards

Vehicle weighing applications in areas rated as Hazardous require special precautions. METTLER TOLEDO offers a variety of load cell and weighing terminal solutions for vehicle applications to meet International hazardous area approval requirements. Contact METTLER TOLEDO for further details.








Vehicle Weighing System Accessories

To complete the vehicle weighing system, an array of peripheral products is availble for seamless integration with the vehicle scale and weighing terminal:

- Automatic Equipment Identification (AEI) readers
- Traffic lights and gates
- Vehicle proximity loop and photo-eye sensors
- Ticket printers
- Remote weight displays
- Custom solutions



Your local vehicle sales specialist can provide further information about accessories to meet the requirements of your application.

www.mt.com/Vehicle

Visit for more information

Mettler-Toledo AG

Sales International CH-8606 Greifensee Switzerland Tel. +41 44 944 22 11 Fax +41 44 944 30 60

Mettler-Toledo Ltd.

64 Boston Road Beaumont Leys Leicester LE4 1AW Tel. 0116 235 7070





Quality certification. Development, production, and auditing in accordance with ISO9001. Environmental management system in accordance with ISO14001.



Service XXL° Tailored Services. Our extensive service network is among the best in the world and ensures maximum availability and service life of your product.



Conformité Européene

This label is your guarantee that our products conform to the latest guidelines.

Subject to technical changes © 09/2010 Mettler-Toledo AG Printed in Switzerland MTSI 44099444